




Properties		Standards		DropDeck	
Technical Characteristics					
Hardness Shore A		ASTM D 2240		Top: 68 Bottom: 59	
Slip Resistance		ASTM D-2047-82		> 0.6	
Critical Radiant Flux		ASTM E648		Class 1	
Smoke Density		ASTM E662		< 450	
Indentation		ASTM F36		< .20mm	
Abrasion Resistance		DIN 53516		< 160mm3	
Tensile Strength		ASTM D412		> 850psi	
Resistance to Chemicals		DIN 51958		Good	
Static Generation		DIN 54345		< 2- Antistatic	
Acoustical Insulation		DIN 52210		10-18db	
Dimensional Characteristics					
Wear Surface				100% Virgin Skate Resistant Rubber	
Base Layer				Recycled and Virgin Rubber Composite	
Thickness	Width	Length	Weight	Area/Roll	WT/Roll
6 mm	4 ft. (1.25 m)	65'6" (20 m) max	1.75 lb/sq.ft.	262 sq. ft. approx.	459 lbs
8 mm	4 ft. (1.25 m)	49' (15 m) max	2.33 lb/sq.ft.	197 sq. ft. approx.	459 lbs
10 mm	4 ft. (1.25 m)	49' (15 m) max	2.91 lb/sq.ft.	197 sq. ft. approx.	573 lbs
Available also in 1 meter (3.28 ft.) square edge or interlocking tiles. (min. order 1,000 sq.ft.)					
Maintenance		 <p>See Tarkett Sports Maintenance Guidelines for more details.</p>			
Standard Colors					



Description :

Dropzone DropDeck is constructed with a calendared High Impact Virgin Rubber surface that is durable and ice skate resistant. The textured surface offers excellent traction and performance under foot. The force reduction base layer is made from a blend of recycled and virgin rubber formed with a basket weave profile providing comfort. This product is ideally suited for weight room, fitness centers, ice skating arenas, locker rooms, and more.

Surface Texture:

Textured for Optimal Traction

Installation instructions and maintenance guide:

On request

Custom Widths :

500 sq. ft. min. for each width ordered



Recycled Content



Compatible Substrates: Properly constructed and prepared Concrete, Wood, Asphalt, and Cementitious Underlayments

Refer to current installation guidelines, ASTM F710, ACI 302.2R, and other industry standard recommendations for more information.

We reserve the right to modify these specifications without affecting their compliance with standards. Some results may slightly vary in relation to certain flexibilities found within specified testing procedures and manufacturing tolerances.



Sustainability: an everyday practice, not just an idea.

Potential LEED Credits:
Tarkett Sports chooses sustainability in concert with performance. Please contact your area representative for assistance.

TARKETT SPORTS
175 N. Industrial Blvd Ne.
Calhoun, Georgia, 30701
888 364-6541
www.tarkettsportsindoor.com