

Omnisports 6.5

Vinyl Indoor Multi-Purpose Point Elastic Sport Flooring

Properties	Standards	Omnisports 6.5 mm		
		Green Lay™	Full Spread Direct Glue	Installation on Tarkolay
Sports Properties				
Surface Finish Effect	ASTM F2772-11	Passed		
Shock Absorption	ASTM F2772-11	Category 2		
Vertical Deformation	ASTM F2772-11	Passed		
Vertical Ball Rebound	ASTM F2772-11	Passed		
Specular Gloss	EN ISO 2813	14.4 %		
Technical Characteristics				
Reaction to Fire	ASTM E648	Class 1 Radiant Panel		
Sound Insulation	ISO 717/02	+/- 19 dB (below room)		
Sound Insulation	NF S31-074	61dB (in room)		
Static Load	ASTM F970	200 p.s.i. (modified)		
Indentation Resistance	EN 1516	0.21 mm	0.40 mm	
Rolling Load	EN 1569	≤ 0,50 mm No degradation		
Resistance to Impact	EN 1517	No degradation		
Taber Abrasion	ASTM D3389	0.02 g (1000 cycles)		
Stain Resistance	ASTM F925	Excellent		
Asthma and Allergy Friendly	ASP: 05-01/101	Certified Compliant		
Surface treatment	Topclean X-treme performance protection			
Maintenance	<p>See current maintenance guidelines for more information</p>			

Key points



Description :

Vinyl sports floor covering over fibreglass mat with PVC foam backing. Protected with Top Clean XP® (dirt-resistant treatment for ease of maintenance)

3 types of installation :

- Green Lay™
- Full Spread Glue
- Installation on Tarkolay

Surface Texture: Slight


Compatible Installation :

Properly constructed concrete and wood substrates. See installation guidelines for more information.

Installation instructions and maintenance guide:

On request


Dimensions (EN 426/EN 427)



Total thickness (EN 428/EN 429) :



Total weight (EN 430) :



Recycled Content 21%



Compatible Substrates: Properly constructed and prepared Concrete, Wood, Asphalt, and Cementitious Underlayments

Refer to current installation guidelines, ASTM F710, ACI 302.2R, and other industry standard recommendations for more information.

We reserve the right to modify these specifications without affecting their compliance with standards. Some results may slightly vary in relation to certain flexibilities found within specified testing procedures and manufacturing tolerances.



Potential LEED Credits:
Tarkett Sports chooses sustainability in concert with performance. Please contact your area representative for assistance.

TARKETT SPORTS
175 N. Industrial Blvd Ne.
Calhoun, Georgia, 30701
888 364-6541
www.tarkettsportsindoor.com