



Properties	Standards	RESICORE RUBBER GY			
Technical Characteristics					
Thickness		6 mm	8 mm	10 mm	
Force Reduction	ASTM F2772	Category 1	Category 1	Category 2	
Ball Bounce	ASTM F2772	Passed	Passed	Passed	
Shore Hardness	ASTM D2240	60	60	60	
Taber Abrasion	ASTM C501	.1848	.1848	.1848	
Tensile Strength	ASTM D412	26	26	25	
Elongation at Break	ASTM D412	255%	255%	247%	
Fire Rating	ASTM E648	Category 1 Passed			
Fungal Resistance	ASTM G21	No Growth			
VOC Compliance	ASTM D5116	Yes			
Dimensional Characteristics					
Wear Surface 2 mm (3mm Optional)		100% Virgin Calendered Rubber			
Base Layer		Recycled and Virgin Rubber Composite			
Total Thickness		5 mm	6 mm	8 mm	10 mm
Wear Surface		2 mm	2 mm	2 mm	2 mm
Width		4 ft	4 ft	4 ft	4 ft
Length		20 m 65.6 ft	20 m 65.6 ft	15 m 49.2 ft	15 m 49.2 ft
Weight		1.35 Lb/sq.ft.	1.60 Lb/sq.ft.	2.13 Lb/sq.ft.	2.67 Lb/sq.ft.
Maintenance	<p>See Tarkett Sports Maintenance Guidelines for more details.</p>				
	<p>Standard Colors</p> <p>Wood Grain Texture</p> <p>Slight Texture</p>				



Description :

Resicore Rubber GY is constructed with a calendared Virgin Rubber surface that is durable and easy to maintain. The textured surface offers excellent traction and performance under foot. The force reduction base layer is made from a blend of recycled and virgin rubber formed with a basket weave profile providing excellent shock absorption and energy return.

Surface Texture:

Available is Wood Grain or Light Texture

Installation instructions and maintenance guide:

On request



Recycled Content
30%

Compatible Substrates: Properly constructed and prepared Concrete, Wood, Asphalt, and Cementitious Underlayments

Refer to current installation guidelines, ASTM F710, ACI 302.2R, and other industry standard recommendations for more information.

We reserve the right to modify these specifications without affecting their compliance with standards. Some results may slightly vary in relation to certain flexibilities found within specified testing procedures and manufacturing tolerances.



Potential LEED Credits:
Tarkett Sports chooses sustainability in concert with performance. Please contact your area representative for assistance.

TARKETT SPORTS
175 N. Industrial Blvd Ne.
Calhoun, Georgia, 30701
888 364-6541
www.tarkettsportsindoor.com