



Properties		Standards		RESICORE RUBBER MP			
Technical Characteristics							
Hardness Shore A	ASTM D 2240		63 (Top Layer)				
Tensile Strength	ASTM D412-98a		3.8				
Elongation (%)	ASTM D412-98a		252				
Coefficient of Friction	ASTM D 1894-2001		1.63				
Chemical Resistance			Good				
Fire Resistance	ASTM E648		Class 1				
Spike Resistance	DIN 18035		Light				
Dimensional Characteristics							
Wear Surface				100% Virgin Spike Resistant Rubber			
Base Layer				Recycled and Virgin Rubber Composite			
Thickness	5 mm	6 mm	8 mm	10 mm	12 mm	13 mm	14 mm
Wear Surface	2 mm	2 mm	2 mm	3 mm	3 mm	5 mm	5 mm
Width	30-49" Max.	30-49" Max.	30-49" Max.	30-49" Max.	30-49" Max.	30-49" Max.	30-49" Max.
Length	20 m 65.6 ft	20 m 65.6 ft	15 m 49.2 ft	15 m 49.2 ft	15 m 49.2 ft	15 m 49.2 ft	15 m 49.2 ft
Weight	1.12 lb/sq.ft.	1.35 lb/sq.ft.	1.79 lb/sq.ft.	2.24 lb/sq. ft.	2.69 lb/sq.ft.	2.91 lb/sq.ft.	3.14 lb/sq.ft.
Maintenance		<p>See Tarkett Sports Maintenance Guidelines for more details.</p>					
Standard Colors							



Description :

Resicore Rubber MP is constructed with a calendared Virgin Rubber surface that is durable and spike resistant. The textured surface offers excellent traction and performance under foot. The force reduction base layer is made from a blend of recycled and virgin rubber formed with a waffle profile providing excellent shock absorption and energy return.

Surface Texture: Highly Textured for traction.

Installation instructions and maintenance guide: On request

Custom Widths : 1000 sq. ft. min. for each width ordered.



Recycled Content
30%



Compatible Substrates: Properly constructed and prepared Concrete, Wood, Asphalt, and Cementitious Underlayments

Refer to current installation guidelines, ASTM F710, ACI 302.2R, and other industry standard recommendations for more information.

We reserve the right to modify these specifications without affecting their compliance with standards. Some results may slightly vary in relation to certain flexibilities found within specified testing procedures and manufacturing tolerances.



Sustainability:
an everyday practice,
not just an idea.

Potential LEED Credits:

Tarkett Sports chooses sustainability in concert with performance. Please contact your area representative for assistance.

TARKETT SPORTS
175 N. Industrial Blvd Ne.
Calhoun, Georgia, 30701
888 364-6541
www.tarkettsportsindoor.com

Version 2.01 07312012