Bona SuperSport Paint®

Waterbased game line paint

Fast drying paint manufactured for use with both Bona® waterborne and oil-modified sport floor sealers and finishes

Bona SuperSport Paint® is a fast drying, waterbased game line paint manufactured for use with both Bona® waterborne and oil-modified sport floor sealers and finishes. Domestically sourced pigments allow for a shelf-life of 18 months and offer better hiding.

- Specifically formulated for sport gamelines, lettering and logos
- Use with Bona® waterborne or oil-modified finishes
- Fast drying with 3-4 hours recoat of finish
- No abrasion needed for adhesion of finish
- VOC compliant
- GREENGUARD Gold Certified

Bona SuperSport Paint®

Waterbased game line paint

Fast drying paint manufactured for use with both Bona® waterborne and oil-modified sport floor sealers and finishes

PHYSICAL CHARACTERISTICS

Ingredients – Polymer, Water, Dipropylene glycol n butyl ether, Dipropylene glycol monoethyl ether, and Pigments
Base Colors – Yellow, Lt. Yellow, Gold, Orange, Red, Maroon, Black, White, League Blue, Dark Blue, N.C. Blue, Purple, Green, Lt. Green, Grey, Brown, Lt. Beige
Odor – Non-offending low odor
Solids – Colors: 32 - 46%
Density – 8.8-10.2 lbs./gallon
US Regulatory VOC – Does not exceed 150 g/L
Stability – 18-month shelf life in unopened container
Packaging – 1-gallon plastic pails

APPLICATION CHARACTERISTICS

Coverage – 400-500 square feet per gallon
Leveling – Excellent
Drying Time – 3-4 hours before coating with waterborne finish, 20-24 hours for oil-modified. A second coat of paint can be applied within 30-90 minutes
Application Tools – Bona NanoFlock Roller, ¼”-nap roller, brush

RECOMMENDED USE

Basketball courts, Multi-purpose gyms, stage, aerobic, dance and yoga floors, volleyball courts, racquetball, squash, and badminton courts.

BEFORE USING, READ ALL DIRECTIONS AND SAFETY DATA SHEETS. KEEP OUT OF REACH OF CHILDREN.

FOR TECHNICAL ADVICE: Call Bona US at 800-872-5515

COMPATIBILITY

Bona SuperSport Paint will adhere to most finishes and sealers after proper preparation and dry times. ALWAYS PREPARE A SAMPLE OR TEST AREA TO DETERMINE COMPATIBILITY. Bona SuperSport Paint is blendable to achieve any custom color desired. Blending rather than tinting, maintains brightness and application characteristics.

SANDING AND PREPARATION OF NEW FLOORS

1. Sand and prepare floor using MFMA-accepted methods. 2. Make your final cut with 100 to 120-grit paper. Screen with 100 or 120-grit screen or use a Bona MultiDisc and 80-grit or 120-grit Bona Diamond abrasives. 3. Vacuum thoroughly. 4. Tack thoroughly with a slightly damp Bona SuperCourt® Athletic Floor Microfiber Wet Cleaning Pad. 5. Apply sealer and finish system (see finish directions).

THE BONA SUPERSPORT PAINT SYSTEM

See sealer instructions for proper sequence of sealer, gamelines and finish coats.

RECOMMENDED APPLICATORS

Bona NanoFlock Roller, ¼”-nap roller, brush

NOTE

Use separate, clean roller/brush for each color of paint.

MIXING INSTRUCTIONS

Remove lid and stir thoroughly before use.

GAMELINES APPLICATION

See sealer instructions for proper sequence of sealer, gamelines and finish coats. Before applying gamelines, abrade the entire floor using 180 or 240-grit Bona Diamond abrasives mounted on 1-2 Bona Conditioning Pads. Vacuum and tack thoroughly. NOTE: If paint will not be applied within 24 hours, the floor must be re-abraded to ensure proper adhesion. Tape gamelines according to industry standards. Apply evenly, using a Bona NanoFlock Roller, brush or 1/4”-nap roller. Apply Bona SuperSport Paint at a rate of 400-500 square feet

Bona SuperSport Paint®

Waterbased game line paint

Fast drying paint manufactured for use with both Bona® waterborne and oil-modified sport floor sealers and finishes

per gallon. More than one coat may be needed. Apply any additional coats once the previous coat is dry to the touch, at least 30-90 minutes. High humidity and/or low temperature conditions will extend the dry time. Recommended conditions are 65-80°F and 40-60% relative humidity. If applying additional stencils or tape over freshly painted surfaces, it is recommended to wait at least 3-4 hours (under recommended conditions) before application. To ensure crisp tape lines, remove tape or stencil within 30 minutes or after 90 minutes. Additional time may be necessary when used outside of recommended climate conditions. To minimize multiple coats of certain colors, Bona SuperSport Light Beige can be used as a first coat primer. Allow paint to dry at least 3-4 hours (under recommended conditions) before coating with finish. When using Bona SuperSport Paint and a Bona waterborne sport finish, there is no need to abrade if coated within 48 hours. If coating with a Bona oil-modified sport finish, allow paint to dry at least 20-24 hours (under recommended conditions). Abrade SuperSport Paint with 1-2 Bona Conditioning Pads. Vacuum and tack thoroughly. Immediately apply finish coats.

NOTE: When working with more than one gallon of the same color, intermix to ensure uniform color. When mixing a custom blend, be sure to mix enough paint for the entire job to ensure uniformity.

CLEAN-UP

Clean application tools and equipment with water

STORAGE AND DISPOSAL

Store at room temperature. Keep container closed when not in use. Do not store above 100˚ F (38˚ C). Do not transfer contents to other containers for storage and disposal. In case of spillage, absorb with inert material. Dispose of contaminated absorbent, container, and unused contents in accordance with local, state, and federal regulations.

ORDERING INFORMATION

Item #	Description	No. Case	Weight/Lbs.
WC660018001	Light Beige	1	10.35
WC660018002	Black	1	9.95
WC660018003	Dark Blue	1	9.5
WC660018005	N.C. Blue	1	9.95
WC660018006	Brown	1	9.75
WC660018007	Gold	1	9.95
WC660018008	Gray	1	10.2
WC660018009	Green	1	9.65
WC660018010	Light Green	1	9.75
WC660018011	Maroon	1	9.65
WC660018012	Orange	1	10.85
WC660018013	Purple	1	9.7
WC660018014	Red	1	10.6
WC660018015	White	1	10.75
WC660018016	Yellow	1	10.05
WC660018017	Light Yellow	1	10.75
WC660018018	League Blue	1	9.0